

MMS

ESS single channel 2 quadrant HV module with floating ground

ESS 10 300n

OK OHVON

04

C

ESS 10 100n

OK HV ON

CO HV-OUT

- ▶ 1 channel, 10 / 20 / 30 kV and customized versions
- > 2-quadrant capabilities, usable as unipolar current sink and source
- perfect for electron optical systems and capacitive loads
- Iow ripple and noise
- floating ground principle
- programmable parameters (delayed trip etc.)

The ESS module is a single channel high voltage power supply in MMS-system (Eurocard format) with 2-quadrant capabilities. It can be used as unipolar current sink and source, which perfectly covers requirements of electron optical systems or capacitive loads.

The ESS series is built in floating ground principle to reduce voltage noise level. The configuration of output voltage and current can be customized on request. The module is made of high precision components such as 24 bit ADC and 16 bit DAC and provides comprehensive security features.





| SPECIFICATIONS / SPEZIFIK | ATION | | | |
|--|---|--|--|--|
| Polarity | factory fixed, positive or negative | | | |
| Ripple and noise | < 0.05 % • V _{nom} | | | |
| Temperature coefficient | < 1 • 10 ⁻⁴ /K | | | |
| Resolution voltage setting | 2 • 10 ⁻⁵ • V _{nom} | | | |
| Resolution voltage measurement | 1 ● 10 ⁻⁵ ● V _{nom} | | | |
| Resolution current measurement | 1 ● 10 ⁻⁵ ● I _{nom} | | | |
| Accuracy voltage measurement * | ± (0.01 % ● V _{nom} + 0.5 % ● V _{out}) | | | |
| Accuracy current measurement * | ± (0.01 % ● I _{nom} + 0.5 % ● I _{out}) | | | |
| Rate of voltage change | up to 0.4 • V_{nom} / s opt. up to 0.75 • V_{nom} / s | | | |
| HV connector | SHV GES | | | |
| Case | 6U cassette, width 8 HP | | | |
| Protection | Safety loop | | | |
| *) All specifications guaranteed from 1% · V < V < V | | | | |

| | CONFIGURATIONS / KONFIGURATIONEN | | | | | | |
|-----|----------------------------------|----------|-------------------|-------------------|-----------------------|--|--|
| | MODEL | CHANNELS | OUTPUT VOLTAGE | OUTPUT CURRENT | RIPPLE AND NOISE | | |
| NEW | ESS 10 100 x | 1 | 10 kV | $\pm 4mA$ | < 5 V _{p-p} | | |
| NEW | ESS 10 200 x | 1 | 20 kV | ± 2mA | < 10 V _{p.p} | | |
| NEW | ESS 10 300 x | 1 | 30 kV | ± 1mA | < 15 V _{p.p} | | |

| ORDER & OPTIONS / BESTELLINFORMATIONEN | | | | | |
|--|---|---------------------|--|--|--|
| OPTION | ORDER INFO | EXAMPLE | | | |
| POLARITY | positive: $\mathbf{x} = \mathbf{p}$, negative: $\mathbf{x} = \mathbf{n}$ | ESS 10 100 p | | | |
| GES CONNECTOR | GES | | | | |



iseg Spezialelektronik GmbH Bautzner Landstr. 23 01454 Radeberg Germany

> phone: +49 351 26996-0 Fax: +49 351 26996-21 e-mail: info@iseg-hv.com

iseg is a manufacturer of very precise and stable High Voltage Power Supplies with focus on physics and industrial applications. The product portfolio includes AC/ DC, DC/DC and modular High Voltage systems. The company was founded in 1995. Continuous growth and innovation strengthened the company's market position. **iseg** is well known for the delevopment of outstanding custom specific solutions for various special applications.

Power4Test GmbH, Grünwalder Weg 13a, 82008 Unterhaching, Germany phone: +49-89-95890293, e-mail: info@power4test.com, web: www.power4test.com

(Central & Eastern European Countries)

Sales & Support Contact: